



## NEW TOOLS

### 41450 INTERMEDIATE PITMAN ARM PULLER

### 41490 PITMAN ARM PULLER FOR M100 SHEPPARD

### 41610 PITMAN ARM PULLER FOR M110 SHEPPARD

Fully Heat-treated, High-strength Cast Steel Tools for Removing Stubborn Pitman Arms.

Helps prevent damage that can be caused by other removal methods. 41450 works on pitman arms on medium duty trucks and other vehicles with pitman arms held on with a nut. 41610 works on Sheppard M110 steering gears found on many Class 6-8 vehicles. 41490 works on Sheppard M100 steering gears found on many Class 6-8 vehicles. For impact use.

41450 Intermediate Pitman Arm Puller. Box. Shipping wt. 5 lbs 10 oz.

41490 Pitman Arm Puller for M100 Sheppard. Box. Shipping wt. 5 lbs.

41610 Pitman Arm Puller for M110 Sheppard. Box. Shipping wt. 10 lbs. 15 oz.



	41450	41490	41610
Drive	1.25"	1.25"	1.25"
Opening Width	2.25"	2.4375"	4"
Inner Width	3.5"	4.12"	4.72"
Inner Height	3"	1.875"	2.9"



### 39120 LOW PROFILE FUEL LINE DISCONNECT FOR FORD, 5/16" & 3/8"

Flexible One Piece Design Works Better Than Two Piece Disconnect Tools.

Works on 5/16" and 3/8" fuel lines found in 2010 and newer Ford vehicles with 1.6L, 2.0L & 3.5 GTDI, and 6.2L Boss engines. May work on other 5/16" and 3/8" applications. Double ended tool is designed to fit the limited clearance between the fuel line and high pressure fuel pump. Made from durable, flexible acetal.

39120 Low Profile Fuel Line Disconnect for Ford, 5/16" & 3/8"  
Skin-Packed. Shipping wt. 1 oz.



## 39100 SPRING LOADED OIL COOLER DISCONNECT SET FOR FORD, 2 PC.

Two Sizes, 3/8" and 1/2", are Designed to Disconnect Transmission Oil Cooler Lines on Ford Vehicles.

The tools have a special stepped design to fit connectors. Simply push the line toward the connector, then engage tool and pull line from connector. Use 3/8" disconnect for 2003 - 2010 Ford V8 Explorer, 2004 and later Ford F150 and Cadillac CS. Use 1/2" disconnect for Ford Super Duty Trucks, F250, F350 and F450.

39100 Spring Loaded Oil Cooler Disconnect Set for Ford, 2 pc.  
Skin-Packed. Shipping wt. 2 oz.

39530 Ford Spring Loaded Oil Cooler Disc. 1/2"

39570 Ford Spring Loaded Oil Cooler Disc. 3/8"



## 61860 TORQUE ADAPTER, 25 NM

Helps Prevent Over Tightening Plastic and Aluminum Oil Filter Canisters and Filters.

Turns any 3/8" drive ratchet or breaker bar into a 25 Newton-meter torque wrench. Can also be used with 21mm socket or wrench. Not for use with impact or pneumatic wrenches.

61860 Torque Adapter, 25 Nm. Box. Shipping wt. 6 oz.

YouTube

