



NEW TOOLS

31610 PRO SHEAR SOCKET, 2-1/8"

2-5/8" O.D. Socket is Used to Remove and Install the Hub Nut on 2021 and Newer Chevrolet Silverado and GMC Sierra With 11-1/2" or 12" Single Rear Wheel Axle Hubs.

May work on other vehicles with 2-1/8" I.D. axle nut/O.D. spindle. Full-floating hubs are held on with a circular nut that is engaged by the 4 pin socket for removal and installation. The 1/2" drive socket is hardened for durability with a black oxide finish. Not for impact use.

31610 Pro Shear Socket, 2-1/8". Box. Shipping wt. 1 lb. 2 oz.



YouTube

31600 PRO SHEAR SOCKET, 2"

2-1/2" O.D. Socket is Used to Remove and Install the Hub Nut on 2021 and Newer Chevrolet Express and GMC Savana With 10-1/2" Dual Rear Wheel Axle Hubs.

May work on other vehicles with 2" I.D. axle nut/O.D. spindle. Full-floating hubs are held on with a circular nut that is engaged by the 4 pin socket for removal and installation. The 1/2" drive socket is hardened for durability with a black oxide finish. Not for impact use.

31600 Pro Shear Socket, 2". Box. Shipping wt. 1 lb.



YouTube

31620 PRO SHEAR SOCKET, 2-3/8"

3" O.D. Socket is Used to Remove and Install the Hub Nut on 2021 and Newer Chevrolet Silverado and GMC Sierra With 11-1/2" or 12" Dual Rear Wheel Axle Hubs.

May work on other vehicles with 2-3/8" I.D. axle nut/O.D. spindle. Full-floating hubs are held on with a circular nut that is engaged by the 4 pin socket for removal and installation. The 1/2" drive socket is hardened for durability with a black oxide finish. Not for impact use.

31620 Pro Shear Socket, 2-3/8". Box. Shipping wt. 1 lb. 8 oz.



YouTube

39790 15/16" RATCHETING FLEX HEAD CAGE BOLT WRENCH

Narrow Head Diameter for Tight Clearance Bolts.



Used when replacing air brake chambers on late model Class 7 and 8 trucks and trailers with Meritor and Bendix disc brakes without removing the wheel. 12-Point, 72 tooth ratcheting flex head and 25" rubber gripped handle provide easy access and extra leverage.

39790 Ratcheting Flex Cage Bolt Wrench, 15/16". Box. Shipping wt. 2 lb. 1 oz.

39760 Flex Head & Bolt



39790 Other Wrenches



YouTube